AMENDMENTS TO THE CLAIMS

This listing of claims replaces all prior versions and listings of claims in the application:

Listing of Claims

- 1-3. (Canceled)
- 4. (Currently Amended) The method of claim 1 claim 51, further comprising transferring the MIPv6-related information from the AAA server in the home network to a home agent.
 - 5-7. (Canceled)
- 8. (Currently Amended) The method of elaim 2 claim 51, wherein the extended authentication protocol for carrying authentication information for network access is an extended Extensible Authentication Protocol (EAP) and the MIPv6-related authentication and authorization information is challenge and response messages are incorporated as additional data in the EAP protocol stack.
- 9. (Currently Amended) The method of claim 8, wherein the MIPv6-related information is transferred in at least one EAP attribute in the EAP protocol stack.
- 10. (Previously Presented) The method of claim 9, wherein the MIPv6-related information is transferred as EAP attributes of the method layer in the EAP protocol stack.
- 11. (Previously Presented) The method of claim 10, wherein the EAP attributes are EAP Type-Length-Value (TLV) attributes.

Attorney Docket No. P18387-US2 Customer Number 27045

12. (Previously Presented) The method of claim 9, wherein the MIPv6-related information is transferred in a generic container attribute available for any EAP method.

13. (Previously Presented) The method of claim 9, wherein the MIPv6-related information is transferred in a method-specific generic container attribute of the method layer in the EAP protocol stack.

14. (Currently Amended) The method of elaim 1 claim 51, wherein the authentication protocol between the mobile node and an AAA client in the visited network is carried by a protocol for carrying authentication information for network access is selected from the group of the Protocol for carrying Authentication for Network Access (PANA), IEEE 802.1X, and Point-to-Point Protocol (PPP).

15. (Canceled)

- 16. (Previously Presented) The method of claim 4, wherein the MIPv6-related information is transferred from the AAA server in the home network to the home agent in an AAA framework protocol application.
- 17. (Previously Presented) The method of claim 16, wherein the home agent is a local home agent in the visited network and the MIPv6-related information is transferred from the AAA home server to the local home agent via an AAA server in the visited network.
- 18. (Currently Amended) The method of claim 15 claim 16, wherein the AAA framework protocol application is an application of a protocol selected from the group of Diameter and RADIUS.

19. (Previously Presented) The method of claim 4, further comprising assigning, by the home AAA server, a home agent to the mobile node; and distributing by the home AAA server to the mobile node and the home agent, credential-related data for establishing a security association between the mobile node and the home agent.

20-21. (Canceled)

22. (Previously Presented) The method of claim 19, further comprising building, at the mobile node, a home address for the mobile node using at least a portion of the address of its assigned home agent; and

transferring the home address of the mobile node from the mobile node to the AAA home network server using around trip of a selected EAP procedure.

23-30. (Canceled)

- 31. (Currently Amended) The system of claim 52, wherein the extended authentication protocol for carrying authentication information for network access is an extended Extensible Authentication Protocol (EAP) and the MIPv6-related authentication and authorization information is challenge and response messages are incorporated as additional data in the EAP protocol stack.
- 32. (Currently Amended) The system of claim 31, wherein the means for transferring the MIPv6-related information comprises is carried in at least one EAP attribute in the EAP protocol stack.
- 33. (Currently Amended) The system of claim 32, wherein the means for transferring the MIPv6-related information comprises is carried in EAP attributes of the method layer in the EAP protocol stack.

Attorney Docket No. P18387-US2 Customer Number 27045

34. (Previously Presented) The system of claim 33, wherein the EAP attributes are EAP Type-Length-Value (TLV) attributes.

35. (Currently Amended) The system of claim 32, wherein the means-for transferring the MIPv6-related information comprises is carried in a generic container attribute available for any EAP method.

36. (Currently Amended) The system of claim 32, wherein means—for transferring the MIPv6-related information emprises is carried in a method-specific generic container attribute of the method layer in the EAP protocol stack.

37. (Currently Amended) The system of claim 24 claim 52, wherein the authentication protocol between the mobile node and an AAA client in the visited network is carried by a protocol for carrying authentication information for network access is selected from the group of the Protocol for carrying Authentication for Network Access (PANA), IEEE 802.1X, and Point-to-Point Protocol (PPP).

38. (Canceled)

- 39. (Currently Amended) The system of elaim 27 claim 52, wherein the MIPv6-related information is transferred from the AAA server in the home network to the a home agent in an AAA framework protocol application.
- 40. (Previously Presented) The system of claim 39, wherein the home agent is a local home agent in the visited network and the MIPv6-related information is transferred from the AAA home server to the local home agent via an AAA server in the visited network.
- 41. (Currently Amended) The system of elaim 38 claim 40, wherein the AAA framework protocol application is an application of a protocol selected from the group of Diameter and RADIUS.

42-50. (Canceled)

51. (New) A method of authentication and authorization support for Mobile IP version 6 (MIPv6), comprising the steps of:

encrypting authentication and authorization information in a mobile node operating in a visited network;

sending the encrypted authentication and authorization information from the mobile node to a pass-through Authentication, Authorization and Accounting (AAA) client in the visited network utilizing a protocol for carrying authentication information for network access;

forwarding the encrypted authentication and authorization information from the AAA client to a visited AAA server in the visited network without analyzing the encrypted authentication and authorization information by the AAA client;

forwarding the encrypted authentication and authorization information from the visited AAA server in the visited network to a home AAA server in the mobile node's home network without analyzing the encrypted authentication and authorization information by the visited AAA server;

performing an analysis of the encrypted authentication and authorization information by the home AAA server;

sending a MIPv6-related challenge message from the home AAA server to the mobile node via the visited AAA server and the pass-through AAA client in the visited network based on the analysis of the encrypted authentication and authorization information, wherein the visited AAA server and the AAA client forward the challenge message without analyzing the challenge message contents;

sending a MIPv6-related challenge response message from the mobile node to the home AAA server via the AAA client and the visited AAA server in the visited network, wherein the AAA client and the visited AAA server forward the challenge response message without analyzing the challenge response message contents;

performing an analysis of the challenge response message contents by the home AAA server; and

sending a MIPv6-related authentication and authorization results message from the home AAA server to the mobile node reporting a result of the analysis of the challenge response message contents and providing session parameter information.

52. (New) A system for authentication and authorization support for MIPv6, comprising:

a mobile node operating in a visited network for encrypting authentication and authorization information and for sending the encrypted authentication and authorization information from the mobile node to a pass-through Authentication, Authorization and Accounting (AAA) node in the visited network utilizing a protocol for carrying authentication information for network access:

the pass-through AAA node for forwarding the encrypted authentication and authorization information to a home AAA server in the mobile node's home network without analyzing the encrypted authentication and authorization information;

the home AAA server for performing an analysis of the encrypted authentication and authorization information and for sending a MIPv6-related challenge message to the mobile node via the pass-through AAA node in the visited network based on the analysis of the encrypted authentication and authorization information, wherein the pass-through AAA node forwards the challenge message without analyzing the challenge message contents;

wherein the mobile node sends a MIPv6-related challenge response message to the home AAA server via the pass-through AAA node in the visited network, wherein the pass-through AAA node forwards the challenge response message without analyzing the challenge response message contents; and

wherein the home AAA server performs an analysis of the challenge response message contents by the home AAA server, and sends a MIPv6-related authentication and authorization results message to the mobile node reporting a result of the analysis of the challenge response message contents and providing session parameter information.